

This User' s manual is only applicable for GPS navigation product.

CPU	Centrality Atlas IV 533MHZ
Flash	32/64/256/512MB/1G/2G/4GBytes
Memory	64MBytes
LCD	5.0 inch TFT screen, resolution:480*272
Touch Screen	High precision touch screen
USB	USB Client 2.0, MINI USB interface
SD	SD/MMC slot, support SD card(maxium 8GB)
Audio frequency	1.1W@8ohm 2.Hi-Fi stereo sound 20mW@32ohm headphone
Keystroke	Sleeping/waking key(power on/off key)
Bluetooth	Built-in bluetooth mould, accord with bluetooth 1.2 standard
GPS	Cold boot:<42 seconds Hot boot:<9 seconds(in the open air) Warm boot:<18 seconds
Battery	Built-in high capacity Lithium battery
Battery charging meatus	DC 5V interface(use together with USB interface)
Power Adaptor	100/220V power adaptor, 5V/1.5A
Car Charger	Turn 12V to 5V/1.5A
LED status	After power adaptor inserts, the battery is in charging (red LED on and green LED off) After power adaptor inserts, the battery charges full (red LED off and green LED on)

Temperature	Working temperature: 0 ° C ~ 60 ° C Storing temperature: -20 ° C ~ 60 ° C
Dimension	
System Platform	Microsoft Windows CE 6.0
Navigation software storing position	SD card
Video Playing software	Support WMV9,MPEG4,Divx 5.0,4.0,3.11,Xvid and MPEG2(maxium image solution:480*272),and AVI, ASF, WMV, RMVB etc.
Audio Playing software	Support WMA9,MP3,WAV file format and LRC
Photo Skimming	E-album,JPG, GIF, BMP and PNG
E-book	TXT format
System setting	Language setting,backlight adjustment,Time setting,Volume adjustment,Power management, Systeme Info
System upgrade	by SD card
Application upgrade	by SD card
Boot-strap Picture Upgrade	by SD card
CPU	Centrality Atlas IV 533MHZ